



mySCHENKER Web Service 2.0.

Services and service description:

Demo:

→ https://webservice.myschenker.fi/TESTewebsecure2_0/webservice2_0.svc

Production:

→ https://webservice.myschenker.fi/ewebsecure2_0/webservice2_0.svc

Collection Point Search

getCollectionPointsByCity: Collection Point Search with city name

getCollectionPointsByPostalCode: Collection Point Search with postal code

getCollectionPointByID: Collection Point Search with a Collection Point ID

Collection Point Shipment Order

createOrder: Collection Point Shipment order

Objective for Collection Point Search Web Service:

The Web Service provides a possibility to search for a DB Schenker collection point based on postal code or city name. Search results will include collection point details like address, opening hours and a unique CollectionPointID which is needed when shipping order is done.

The Web Service provides a possibility to search with a unique CollectionPointID in order to receive collection point details for the specific collection point.

Objective for Collection Point Shipment Order Web Service:

The Web Service provides a possibility to create an order for Collection Point Shipment. Response from the service includes Consignment number for the order and URL-link to piece label (pdf).

Access to Demo Web Service:

User ID and access key to demo Web Service can be provided by request.

Access to production Web Service:

Approval and access to production Web Service can be granted after test results in Demo environment have been approved by

Collection Point Search requests:

Collection Point Search with postal code or city.

```
getCollectionPointsByCity(Authentication auth, string pCity) : List<CollectionPoint>
```

Collection Point Search with postal code

```
getCollectionPointsByPostalCode(Authentication auth, string postalCode) : List<CollectionPoint>
```

Collection Point Search with a Collection Point ID

```
getCollectionPointByID(Authentication auth, string cpID): CollectionPoint
```

Request:

```
<xs:complexType name="Authentication">
  <xs:sequence><xs:element name="accessKey" type="xs:string" nillable="true"/>
  <xs:element name="userName" type="xs:string" nillable="true"/>
</xs:sequence>
```

Field Name	Type	Description	Comments
pCity	string	City name	
postalCode	string	Postal code	
cpID	string	Collection point ID	
Field Name	Type	Description	Comments
accessKey	string	Access Key	
userName	string	User Name	

Collection Point Search responses: CollectionPoint, List<CollectionPoint>

Response Declaration:

```
<xs:complexType name="ArrayOfCollectionPoint">
  <xs:sequence>
    <xs:element name="CollectionPoint" type="tns:CollectionPoint" nillable="true" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfCollectionPoint" type="tns:ArrayOfCollectionPoint" nillable="true"/><xs:complexType name="CollectionPoint">
  <xs:sequence>
    <xs:element name="Address1" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="Address2" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="BusinessHours" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="BusinessHours1" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="BusinessHours2" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="BusinessHours3" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="City" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="CollectionPointID" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="CollectionPointName" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="ContactPerson" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="Distribution" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="Extra" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="Phone" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="PostalCode" type="xs:string" nillable="true" minOccurs="0"/><xs:element name="ProposalOrder" type="xs:int" minOccurs="0"/>
    <xs:element name="Terminal" type="xs:string" nillable="true" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="CollectionPoint" type="tns:CollectionPoint" nillable="true"/>
```

Response Fields

Field Name	Type	Description	Comments
Address1	string	Collection point address line 1	
Address2	string	Collection point address line 2	
BusinessHours	string	Collection point opening hours in format V0000-0000L0000-0000S0000-0000	V: Monday-Friday L: Saturday S: Sunday
BusinessHours1	string	Collection point opening hours for Monday-Friday	
BusinessHours2	string	Collection point opening hours for Saturday	
BusinessHours3	string	Collection point opening hours for Sunday	
City	string	City of collection point	
CollectionPointID	string	Collection point ID	
CollectionPointName	string	Collection point name	
ContactPerson	string	Contact person for collection point	
Distribution	string		
Extra	string	Country Code	
Phone	string	Phone number for collection point	
ProposalOrder	int	Proposal order for suitable collection point. 0 if not in proposal order	
PostalCode	string	Postal code for collection point	
Terminal	string	DB Schenker Terminal number	

Response: SOAP/XML Example

The following code shows an example of a response message returned to the client by the Web Service.

```
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Body>
    <getCollectionPointsByPostalCodeResponse xmlns="http://myschenker.fi/ewebs/">
      <getCollectionPointsByPostalCodeResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
        <CollectionPoint>
          <Address1>RUNEBERGINKATU 41</Address1>
          <Address2/>
          <BusinessHours>V0700-2100L0900-2100S1000-2100</BusinessHours>
          <BusinessHours1>0700-2100</BusinessHours1>
          <BusinessHours2>0900-2100</BusinessHours2>
          <BusinessHours3>1000-2100</BusinessHours3>
          <City>HELSINKI</City>
          <CollectionPointID>6002</CollectionPointID>
          <CollectionPointName>R-KIOSKI HKI RUNEBERGINKATU 41</CollectionPointName>
          <ContactPerson/>
          <Distribution></Distribution>
          <Extra>FI</Extra>
          <Phone>050-3680410</Phone>
          <PostalCode>00100</PostalCode>
          <ProposalOrder>1</ProposalOrder>
          <Terminal>001</Terminal>
        </CollectionPoint>
        <CollectionPoint>
          <Address1>TÖÖLÖNLAHDENKATU 2</Address1>
          <Address2/>
          <BusinessHours>V0700-2000L0900-1900S0000-0000</BusinessHours>
          <BusinessHours1>0700-2000</BusinessHours1>
          <BusinessHours2>0900-1900</BusinessHours2>
          <BusinessHours3>0000-0000</BusinessHours3>
          <City>HELSINKI</City>
          <CollectionPointID>6835</CollectionPointID>
          <CollectionPointName>R-KIOSKI HKI SANOMATALO</CollectionPointName>
          <ContactPerson/>
          <Distribution></Distribution>
          <Extra>FI</Extra>
          <Phone>046-9204204</Phone>
          <PostalCode>00100</PostalCode>
          <ProposalOrder>2</ProposalOrder>
          <Terminal>001</Terminal>
        </CollectionPoint>
      </getCollectionPointsByPostalCodeResult>
    </getCollectionPointsByPostalCodeResponse>
  </s:Body>
</s:Envelope>
```

Collection Point Order Request:

```

<xs:complexType name="CollectionPointOrder">
  <xs:sequence>
    <xs:element name="Authentication" type="tns:Authentication" nillable="true"/>
    <xs:element name="CashOnDelivery" type="xs:double" minOccurs="0"/>
    <xs:element name="CollectionPointID" type="xs:string" nillable="true"/>
    <xs:element name="CustomerNumber" type="xs:string" nillable="true"/>
    <xs:element name="PackageVolume" type="xs:double" minOccurs="0"/>
    <xs:element name="PackageWeight" type="xs:double"/>
    <xs:element name="PickupAddress" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="PickupAddress2" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="PickupCity" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="PickupName" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="PickupPostalCode" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="ReceiverAddress" type="xs:string" nillable="true"/>
    <xs:element name="ReceiverCity" type="xs:string" nillable="true"/>
    <xs:element name="ReceiverContact" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="ReceiverName" type="xs:string" nillable="true"/>
    <xs:element name="ReceiverPhone" type="xs:string" nillable="true"/>
    <xs:element name="ReceiverPostalCode" type="xs:string" nillable="true"/>
    <xs:element name="ReceiverReference" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="SenderReference" type="xs:string" nillable="true" minOccurs="0"/>
    <xs:element name="TradeName" type="xs:string" nillable="true" minOccurs="0"/>
  </xs:sequence>
  <xs:complexType name="Authentication">
    <xs:sequence>
      <xs:element name="accessKey" type="xs:string" nillable="true"/>
      <xs:element name="userName" type="xs:string" nillable="true"/>
    </xs:sequence>
  </xs:complexType>
</xs:complexType>

```

Field Name	Type		Description	Field length / format	Comments
CashOnDelivery	double	O	Cash on Delivery amount—requires agreement	####.##	Max 2 decimals
CollectionPointID	string		Collection point ID	4	
CustomerNumber	string		Customer Number	1-8	
PackageVolume	double	O	Package volume	#.###	Max 3 decimals
PackageWeight	double		Package weight	##.#	Max 1 decimal
PickupAddress	string	O/M	Pick Up Address	0-35	Mandatory If Pickup Address is given
PickupAddress2	string	O	Pick Up Address 2	0-35	
PickupCity	string	O/M	Pick Up City	0-30	Mandatory If Pickup Address is given
PickupName	string	O/M	Pick Up Company Name	0-50	Mandatory If Pickup Address is given
PickupPostalCode	string	O/M	Pick Up Postal Code	5	Mandatory If Pickup Address is given
ReceiverAddress	string		Receiver Address	1-35	
ReceiverCity	string		Receiver City	1-30	
ReceiverContact	string	O	Receiver Contact	0-50	
ReceiverName	string		Receiver Name	1-50	
ReceiverPhone	string		Receiver Phone	1-30	
ReceiverPostalCode	string		Receiver Postal Code	5	
ReceiverReference	string	O	Receiver Reference	0-30	
SenderReference	string	O	Sender Reference	0-30	
TradeName	string		Trade name, content description	1-21	
Field Name	Type		Description		Comments
accessKey	string		Access Key		
userName	string		User Name		

Request SOAP/XML Example

The following code shows an example of a request message sent to the Web Service by client.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/" xmlns:eweb="http://myschenker.fi/ewebs/">
  <soapenv:Header/>
  <soapenv:Body>
    <eweb:createOrder>
      <!--Optional:-->
      <eweb:order>
        <eweb:Authentication>
          <eweb:accessKey>444-333-222-$$$</eweb:accessKey>
          <eweb:userName>DEMO</eweb:userName>
        </eweb:Authentication>
        <!--Optional:-->
        <eweb:CashOnDelivery>0</eweb:CashOnDelivery>
        <eweb:CollectionPointID>1000</eweb:CollectionPointID>
        <eweb:CustomerNumber>000000</eweb:CustomerNumber>
        <!--Optional:-->
        <eweb:PackageVolume>0.144</eweb:PackageVolume>
        <eweb:PackageWeight>1</eweb:PackageWeight>
        <eweb:ReceiverAddress>Address1</eweb:ReceiverAddress>
        <eweb:ReceiverCity>ESPOO</eweb:ReceiverCity>
        <!--Optional:-->
        <eweb:ReceiverContact>CONTACT</eweb:ReceiverContact>
        <eweb:ReceiverName>Receiver</eweb:ReceiverName>
        <eweb:ReceiverPhone>4444</eweb:ReceiverPhone>
        <eweb:ReceiverPostalCode>02280</eweb:ReceiverPostalCode>
        <!--Optional:-->
        <eweb:ReceiverReference>rRef</eweb:ReceiverReference>
        <!--Optional:-->
        <eweb:SenderReference>sRef</eweb:SenderReference>
        <!--Optional:-->
        <eweb:TradeName>Fabrics</eweb:TradeName>
      </eweb:order>
    </eweb:createOrder>
  </soapenv:Body>
</soapenv:Envelope>
```

Response: SOAP/XML Example

The following code shows an example of a response message returned to the client by the Web Service.

```
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Body>
    <createOrderResponse xmlns="http://myschenker.fi/ewebs/">
      <createOrderResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
        <ConsignmentNumber>988003000001</ConsignmentNumber>
        <LabelURL>https://webservice.myschenker.fi/TESTewebsecure/pdfs/NPKolilaput_988003000001_0MTssWW2S20J9S6S.pdf</LabelURL>
      </createOrderResult>
    </createOrderResponse>
  </s:Body>
</s:Envelope>
```

Collection Point Shipment order—response:

Response:

```
<xs:complexType name="CollectionPointReturn">
<xs:sequence><xs:element name="ConsignmentNumber" type="xs:string" nillable="true" minOccurs="0"/>
<xs:element name="LabelURL" type="xs:string" nillable="true" minOccurs="0"/>
</xs:sequence>
```

Field Name	Type	Description	Comments
ConsignmentNumber	String	Consignment Number	
LabelURL	string	Label URL: link to piece label (pdf)	

NOUTOPISTELÄHETYS

DB SCHENKER

Toimitusosoite

**R-KIOSKI ESPOO KUITINMÄKI
KUUNKEHRÄ 4
02210 ESPOO**

Pnro: 02210

Yritys-ID:

Lähetys-ID: 988003811587

Viite: RREF

Paino: 1 kg





988003811587

Vastaanottaja: RECEIVER
CONTACT

Puhelin: 4444

Pakettiennakko: 0,00 EUR

Noutopiste:

6073

FI

Lähetittäjä:
DB SCHENKER DEMO
TIKKURILANTIE 147
01530 VANTAA

Puhelin:

Päiväys:
13.4.2016
myschenker.fi